



ECS4000

HIGH VOLTAGE STORAGE BATTERY



- 3.97kWh capacity
- Scalable to 27.8kWh
- 90% Depth of Discharge
- Wide Temperature Tolerance
- CAN communication
- Voltage Range up to 459.9V



EASY
INSTALLATION



HIGH
EFFICIENCY



EXPANDABLE
SYSTEM



90%
DOD

The ECS is a high-performance, scalable battery storage system. The modular design allows for maximum flexibility, making it suitable for a broad range of storage applications.

Additional batteries can be installed in series, allowing for a maximum storage capacity of 27.8kWh. Installation is easy, with a plug and play solution that can save valuable time for installers.



For more information about the Fox ESS range, visit:
us.fox-ess.com



TECHNICAL SPECIFICATIONS

MODEL	ECS4000-H2	ECS4000-H3	ECS4000-H4	ECS4000-H5	ECS4000-H6	ECS4000-H7
ELECTRICAL CHARACTERISTICS						
Battery Type	LiFePO ₄ Prismatic Cell					
Battery Module	1*CM4000	1*CM4000	1*CM4000	1*CM4000	1*CM4000	1*CM4000
	1*CS4000	2*CS4000	3*CS4000	4*CS4000	5*CS4000	6*CS4000
Nominal Capacity [kWh]	7.95	11.92	15.9	19.87	23.85	27.82
Nominal Voltage [V]	115.2	172.8	230.4	288	345.6	403.2
Operating Voltage [V]	97.2~131.4	145.8~197.1	194.4~262.8	243~328.5	291.6~394.2	340.2~459.9
Max. Charge / Discharge Current [A]	50					
Peak Discharge Current [A]	65 @60sec					
Round-trip Efficiency [%]	>95					
Depth of Discharge [%]	90					
Communication	CAN					
Display	CS: LED*1, CM: LED*6					
Scalability	Max. 7 Modules in Series					
OPERATING CONDITIONS						
Installation Location	Outdoor / Indoor (Stand)					
Operating Temperature [°F / °C]	14 ~ +131 / -10 ~ +55 (Derating above 104 / 40)					
Storage Temperature [°F / °C]	-4 ~ +131 / -20 ~ +55					
Cooling Method	Natural Convection					
Humidity [%]	0 ~ 100 (No condensation)					
Altitude [m / ft]	Max. 2,000 / 6,560					
MECHANICAL CHARACTERISTICS						
Dimensions (W*H*D) [mm]	570*350*380	570*470*380	570*590*380	570*710*380	570*830*380	570*950*380
Dimensions (W*H*D) [inch]	22.4*13.8*15.0	22.4*18.5*15.0	22.4*23.2*15.0	22.4*28.0*15.0	22.4*32.7*15.0	22.4*37.4*15.0
Weight [kg/lbs]	73.5 / 161.7	108.4 / 238.5	143.3 / 315.3	178.2 / 392	213.1 / 468.8	248 / 545.6
CERTIFICATES						
Safety	UL1973, UL9540, UL9540A					
Transportation	UN38.3					
Ingress Protection	IP65					
WARRANTY						
Standard Warranty [year]	12.5*1					

*1, Refer to Fox ESS Battery Warranty Terms and Conditions.

